

**200<sup>+</sup>** 切削條件表 **P385**  
Cutting Condition

## Square Type - Long Flute - Multiple Flutes

### 多刃長刃強力立銼刀



**200 PLUS**

**HRC ▶ 65**



● Super Ultra Fine Micro Grain Carbide

● WC=91 Co=9 HRA=93.2 Rupture=4000N/mm<sup>2</sup> Grain Size=0.2μm



Dimension 規格					Purchase Code 採購代碼		
Diameter	Flute Length	Full Length	Shank Diameter	Flutes	MODE	Coating 塗層	
d 刃徑	刀長	L 全長	D 柄徑	Z 刃數	型號	TiSiN+	P-nACo
6	25	75	6	5	P-SFULVT0605	.06	.07
8	35	100	8	7	P-SFULVT0807	.06	.07
10	45	100	10	7	P-SFULVT1007	.06	.07
12	50	100	12	7	P-SFULVT1207	.06	.07
16	65	150	16	9	P-SFULVT1609	.06	.07
20	75	150	20	9	P-SFULVT2009	.06	.07
25	80	150	25	9	P-SFULVT2509	.06	.07

HRC ▶ 40

HRC ▶ 45

HRC ▶ 50

HRC ▶ 55

HRC ▶ 60

HRC ▶ 65

Application 適用材質：

★ Perfect 最推薦    ◎ Excellent 適合    ○ Good 佳

Coating 塗層	Carbon steel, Alloy steel 炭素鋼, 合金鋼	Pre-hardened steel 預硬鋼	High-hardened 高硬度鋼				Stainless steel 不鏽鋼	Titanium alloy 鈦合金	Nickel/Inconel alloy 鎳基合金	Copper alloy 銅合金, 銅	Aluminum alloy 鋁合金
		~45HRC	~50HRC	~55HRC	~60HRC	~65HRC					
TiSiN+	○	○	○	◎	◎	◎					
P-nACo	○	○	○	◎	◎	★					

Unit/單位: mm